

EUROLUB DOPPELKUPPLUNGSFLUID DKG

Description

DKG DUAL-CLUTCH FLUID is specifically designed to meet the requirements of high-tech dual-clutch transmissions, which are becoming increasingly prominent in the automotive industry, and is particularly suitable for dual-clutch transmissions with a single oil circuit, in which the clutch, synchronisers, gear set and hydraulic control system all use the same oil.

Appearance: yellow

Can be used with

VW G-052-529 / VW G-052-182
BMW 83222148578/83222148579
BMW 83220440214/83222147477
Ford WSS-M2C-936-A
DTFR 13C130
MB 236.25
Mitsubishi MZ320065
PSA 9734.S2
Porsche 999.917.080.00
Volvo 1161838 / 1161839

Audi G 052 529 A2
Audi G 055 529 A2
BMW 83 22 2 148 578
Chrysler 68044345EA
Citroen 9734.S2
Ford 1 490 763
Land Rover GX73-M1R564-AA
MB 001 989 85 03
Peugeot 9734.S2
Porsche 000 0 43 207 30
Seat G 052 182 A2
Seat G 055 529 A2
Skoda G 052 182 A2
Skoda G 055 529 A2
VW G 052 529 A2
VW G 055 529 A2

Delivery

Art.-No. 545001	12 x 1 Liter	bottle
Art.-No. 545020	20 Liter	can
Art.-No. 545060	60 Liter	drum
Art.-No. 545208	208 Liter	drum
Art.-No. 545100	Container	800 – 3.000 litre
Art.-No. 545000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.850
Viscosity at 40°C	mm ² /s	DIN 51 562	34.5
Viscosity at 100°C	mm ² /s	DIN 51 562	7.2
Viscosityindex (VI)	-	DIN ISO 2909	181
Flash point (COC)	°C	DIN ISO 2592	216
Pourpoint	°C	DIN ISO 3016	-51