

Saw Chain Oil 100

Description

Mineral-based high-performance oil for once-through loss lubrication. Thanks to the outstanding adhesion properties and first-class lubricating effect, provides optimum protection of moving parts such as chain links and joints against wear and corrosion. Ensures year-round use at all outside temperatures based on its favorable viscosity characteristics.



Properties

- outstanding lubricating action
- outstandingly adherent
- excellent low temperature behavior
- excellent viscosity/temperature properties

Available pack sizes

60 l Black plate barrel 1191
D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

ISO viscosity class	100 DIN 51519
Density at 15 °C	0,87 g/cm ³ DIN 51757
Viscosity at 40 °C	100 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	13,2 mm ² /s ASTM D 7042-04
Viscosity index	130 DIN ISO 2909
Pour point	-39 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Oxide ash	0,5 g/100g DIN EN ISO 6245
Color / appearance	grau-schwarz

Areas of application

For lubricating chains on chainsaws, reciprocating saws, etc. Also suitable for extreme applications such as sawing hardwoods.

Application

The specifications and instructions from the unit or chain manufacturer must be followed.

Available pack sizes

1 l Canister plastic	1277 D-BOOKLET
5 l Canister plastic	1278 D-BOOKLET