EUROLUB
HLP ISO-VG 46 EL

Description

HLP 46 EL is formulated from paraffin-based base oils and state-of-the-art additive technology. Effective zinc-containing components ensure optimum lubrication performance and long-lasting protection against ageing.
HLP 46 EL is particularly notable for its high electrical conductivity.

Can be used with

DIN 51 524 / Teil 2
ISO 11158
ASTM D6158

Delivery

Art.-No. 505208	208 Liter	drum
Art.-No. 505100	Container	800 – 3.000 litre
Art.-No. 505000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.857
Viscosity at 40°C	mm²/s	DIN 51 562	43.0
Viscosity at 100°C	mm²/s	DIN 51 562	7.0
Viscosityindex (VI)	-	DIN ISO 2909	119
Flash point (COC)	°C	DIN ISO 2592	240
Pourpoint	°C	DIN ISO 3016	-30
EL. Conductivity @24°C	µS/m	ASTM D2624	750

Die angegebenen Daten können Änderungen unterliegen. Betriebsvorschriften des Herstellers beachten. Durch Weiterentwicklung von Produkt und Produktion bedingte Datenänderungen bleiben vorbehalten. Diese Angaben sollen das Produkt beschreiben und haben somit nicht die Bedeutung, bestimmte Eigenschaften zuzusichern. Eine Verbindlichkeit kann hieraus nicht abgeleitet werden.

KLIMANEUTRALES UNTERNEHMEN
certified by Fokus Zukunft