Product information
Rapid Rust Solvent

PI 16/01/29/2025

Description
Extremely fast rust solvent. Rapidly frees seized bolts and nuts. Penetrates even the narrowest of openings. Rust is penetrated and dissolved.

Properties
- dissolves rust
- outstanding resistance to salt water
- good corrosion protection
- does not attack plastics, paints and metals
- penetrtes fast
- low coefficient of friction
- releases dirt

Technical data

Form	liquid
Base	combination of oils, agents
Color / appearance	brown
Odor	characteristic
Density at 20 °C	0,84 g/cm³
Viscosity at 40 °C	< 7 mm²/s
Flash point	62 °C
Solubility in water	soluble
Operating temperature range	- 40°C to + 140°C °C
Spreading rate (cover)	sheet steel, bright 140-180 m²/l
Base	combination of oils, agents
Color / appearance	brown
Density at 20 °C	0,84 g/ml DIN 51757
Operating temperature range	-40 bis +140 °C
Form	liquid
Odor	characteristic

Areas of application
The outstanding characteristics of EPRO Rust Solvent allow the product to be used in a wide variety of applications in operations, in the workshop, on motorized vehicles and on all household and hobby appliances.

Application
Spray with the air spray can or spray gun or apply by immersion, brush or wiping.

Available pack sizes

Available pack sizes

5 l Canister plastic	3611
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com