

EUROLUB CGLP ISO-VG 68

Description

CGLP is formulated using high-quality base oils and modern additives. Its active ingredients ensure optimum lubrication performance and oxidation protection. It offers good sliding properties and high adhesion. Its corrosion-protective properties prevent rust and staining on sliding surfaces and guideways.

The product is resistant to aqueous media such as drilling, cutting and grinding emulsions.

- Very good stick-slip behaviour
- Good demulsifying properties
- High adhesion

Can be used with

DIN 51 502

Delivery

Art.-No. 350001	20 Liter	can
Art.-No. 350005	20 Liter	can
Art.-No. 350020	20 Liter	can
Art.-No. 350060	60 Liter	drum
Art.-No. 350208	208 Liter	drum
Art.-No. 350100	Container	800 – 3.000 litre
Art.-No. 350000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.880
Viscosity at 40°C	mm ² /s	DIN 51 562	67.1
Viscosity at 100°C	mm ² /s	DIN 51 562	8.5
Viscosityindex (VI)	-	DIN ISO 2909	90
Flash point (COC)	°C	DIN ISO 2592	245
Pourpoint	°C	DIN ISO 3016	-27