

SAFETY DATA SHEET

NITRO THINNER

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: NITRO THINNER

Product no.: 100126xxn

Unique formula identifier 0RYE-QV6M-S20Q-7N8V

(UFI):

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses None known.

*of the substance or
mixture:*

Use descriptors (REACH):

Product category	Description
PC 0	Other products

Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **EUROLUB GmbH**
Freisingerstraße 25-27
85386 Eching
Germany
Tel.: +49 8165 9591-0
www.eurolub.com

Contact person: Laboratory

E-mail: info@eurolub.com

▼ *Revision:* 06/07/2026

▼ *SDS Version:* 2.0

▼ *Date of previous version:* 02/08/2023 (1.0)

1.4. Emergency telephone number

Phone: +49 8165 9591-0

This number is only available at office times.

SECTION 2: HAZARDS IDENTIFICATION

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. ▼ Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Dam. 1; H318, Causes serious eye damage.

STOT SE 3; H335, May cause respiratory irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. ▼ Label elements

Hazard pictogram(s):



Signal word: Danger

▼ *Hazard statement(s):* Highly flammable liquid and vapour. (H225)
May be fatal if swallowed and enters airways. (H304)
Causes skin irritation. (H315)
Causes serious eye damage. (H318)
May cause respiratory irritation. (H335)

May cause drowsiness or dizziness. (H336)
May cause damage to organs through prolonged or repeated exposure. (H373)
Harmful to aquatic life with long lasting effects. (H412)

▼ *Precautionary*

statement(s):

General: If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

▼ *Prevention:*

Do not breathe vapour/mist. (P260)

Wear face protection/protective gloves/protective clothing. (P280)

▼ *Response:*

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
(P305+P351+P338)

▼ *Storage:*

Not applicable.

Disposal:

Dispose of contents/container in accordance with local regulations
(P501)

▼ *Hazardous substances:*

reaction mass of ethylbenzene and xylene

n-butyl acetate

2-methoxy-1-methylethyl acetate

1-methoxy-2-propanol;monopropylene glycol methyl ether

▼ *Additional labelling:*

UFI: 0RYE-QV6M-S20Q-7N8V

▼ *Labelling of contents*

according to Detergents ≥15% - <30%

Regulation (EC) No · Aliphatic hydrocarbons

648/2004 (applicable to · Aromatic hydrocarbons

packaging of detergents

sold to the general

public):

▼ VOC: VOC content: 836 g/L
MAXIMUM VOC CONTENT (Phase II, category B/a1: 850 g/L)

2.3. Other hazards

▼ *Additional warnings:* This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
The substance(s) shown below are considered/suspected to be endocrine disruptors according to the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707:
butanone;ethyl methyl ketone

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	CAS No.: EC No.: 921-024-6 UK-REACH: 01-2119475514-35-XXXX Index No.:	10-15%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	
reaction mass of ethylbenzene and xylene	CAS No.: EC No.: 905-588-0 UK-REACH: 01-2119486136-34-XXXX Index No.:	10-15%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	
acetone;propan-2-one;propanone	CAS No.: 67-64-1 EC No.: 200-662-2 UK-REACH: 01-2119471330-49-XXXX Index No.: 606-001-00-8	10-15%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

n-butyl acetate	CAS No.: 123-86-4 EC No.: 204-658-1 UK-REACH: 01-2119485493-29-XXXX Index No.: 607-025-00-1	5-10%	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336	[1]
Hydrocarbons, C9, aromatics	CAS No.: 128601-23-0 EC No.: 918-668-5 UK-REACH: 01-2119455851-35-XXXX Index No.:	5-10%	EUH066 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 2, H411	
2-methoxy-1-methylethyl acetate	CAS No.: 108-65-6 EC No.: 203-603-9 UK-REACH: 01-2119475791-29-XXXX Index No.: 607-195-00-7	5-10%	Flam. Liq. 3, H226	[1]
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: 01-2119457558-25-XXXX Index No.: 603-117-00-0	5-10%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
1-methoxy-2-propanol;monopropylene glycol methyl ether	CAS No.: 107-98-2 EC No.: 203-539-1 UK-REACH: 01-2119457435-35-XXXX Index No.: 603-064-00-3	5-10%	Flam. Liq. 3, H226 STOT SE 3, H336	[1]
butanone;ethyl methyl ketone	CAS No.: 78-93-3 EC No.: 201-159-0 UK-REACH: 01-2119457290-43-XXXX Index No.: 606-002-00-3	5-10%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
2-methylpropan-1-ol;isobutanol	CAS No.: 78-83-1 EC No.: 201-148-0 UK-REACH: 01-2119484609-23-XXXX Index No.: 603-108-00-1	5-10%	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	
ethyl acetate	CAS No.: 141-78-6 EC No.: 205-500-4 UK-REACH: 01-2119475103-46-XXXX Index No.: 607-022-00-5	3-5%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

- General information:* In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.
- ▼ *Inhalation:* IF INHALED: Move to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or a doctor.
- Skin contact:* Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.
- ▼ *Eye contact:* If in eyes: Flush eyes with plenty of water or saline solution (20-30 °C) for at least 30 minutes and continue until irritation stops.
Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.
- Ingestion:* IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns: Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed.

Symptoms of chemical pneumonia may appear after several hours.

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health.

Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. ▼ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. ▼ Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼ Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material: Always store in containers of the same material as the original container.

Storage conditions: Dry, cool and well ventilated

Incompatible materials: Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. ▼ Control parameters

acetone;propan-2-one;propanone

Long term exposure limit (8 hours) (ppm): 500

Long term exposure limit (8 hours) (mg/m³): 1210

Short term exposure limit (15 minutes) (ppm): 1500

Short term exposure limit (15 minutes) (mg/m³): 3620

n-butyl acetate

Long term exposure limit (8 hours) (ppm): 150

Long term exposure limit (8 hours) (mg/m³): 724

Short term exposure limit (15 minutes) (ppm): 200

Short term exposure limit (15 minutes) (mg/m³): 966

propan-2-ol;isopropyl alcohol;isopropanol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m³): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m³): 1250

butanone;ethyl methyl ketone

Long term exposure limit (8 hours) (ppm): 200

Long term exposure limit (8 hours) (mg/m³): 600

Short term exposure limit (15 minutes) (ppm): 300

Short term exposure limit (15 minutes) (mg/m³): 899

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-methylpropan-1-ol;iso-butanol

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 154

Short term exposure limit (15 minutes) (ppm): 75

Short term exposure limit (15 minutes) (mg/m³): 231

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

2-methylpropan-1-ol;iso-butanol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	55 mg/m ³
Long term – Local effects - Workers	Inhalation	310 mg/m ³

acetone;propan-2-one;propanone

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	186 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	200 mg/m ³
Long term – Systemic effects - Workers	Inhalation	1210 mg/m ³
Short term – Local effects - Workers	Inhalation	2420 mg/m ³
Long term – Systemic effects - General population	Oral	62 mg/kg bw/day

butanone;ethyl methyl ketone

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	412 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	1161 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	106 mg/m ³
Long term – Systemic effects - Workers	Inhalation	600 mg/m ³
Short term – Systemic effects - General population	Inhalation	450 mg/m ³
Short term – Systemic effects - Workers	Inhalation	900 mg/m ³

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Long term – Systemic effects - General population	Oral	31 mg/kg bw/day
---	------	-----------------

Hydrocarbons, C9, aromatics

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	7.5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	12.5 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	32 mg/m ³
Long term – Systemic effects - Workers	Inhalation	151 mg/m ³
Long term – Systemic effects - General population	Oral	7.5 mg/kg bw/day

n-butyl acetate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	3.4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	7 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	6 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	11 mg/kg bw/day
Long term – Local effects - General population	Inhalation	35.7 mg/m ³
Long term – Local effects - Workers	Inhalation	300 mg/m ³
Long term – Systemic effects - General population	Inhalation	12 mg/m ³
Long term – Systemic effects - Workers	Inhalation	48 mg/m ³
Short term – Local effects - General population	Inhalation	300 mg/m ³
Short term – Local effects - Workers	Inhalation	600 mg/m ³
Short term – Systemic effects - General population	Inhalation	300 mg/m ³
Short term – Systemic effects - Workers	Inhalation	600 mg/m ³
Long term – Systemic effects - General population	Oral	2 mg/kg bw/day
Short term – Systemic effects - General population	Oral	2 mg/kg bw/day

propan-2-ol;isopropyl alcohol;isopropanol

Duration:	Route of exposure:	DNEL:
-----------	--------------------	-------

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m ³
Long term – Systemic effects - Workers	Inhalation	500 mg/m ³
Short term – Systemic effects - General population	Inhalation	178 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1000 mg/m ³
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

▼ PNEC

2-methylpropan-1-ol;iso-butanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		400 µg/L
Freshwater sediment		1.56 mg/kg
Intermittent release (freshwater)		11 mg/L
Marine water		40 µg/L
Marine water sediment		156 µg/kg
Sewage treatment plant		10 mg/L
Soil		76.5 µg/kg

acetone;propan-2-one;propanone

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		10.6 mg/L
Freshwater sediment		30.4 mg/kg
Intermittent release (freshwater)		21 mg/L
Marine water		1.06 mg/L
Marine water sediment		3.04 mg/kg
Sewage treatment plant		100 mg/L
Soil		29.5 mg/kg

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

butanone;ethyl methyl ketone

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		55.8 mg/L
Freshwater sediment		284.74 mg/kg
Intermittent release (freshwater)		55.8 mg/L
Marine water		55.8 mg/L
Marine water sediment		284.7 mg/kg
Predators		1 g/kg
Sewage treatment plant		709 mg/L
Soil		22.5 mg/kg

n-butyl acetate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		180 µg/L
Freshwater sediment		981 µg/kg
Intermittent release (freshwater)		360 µg/L
Marine water		18 µg/L
Marine water sediment		98.1 µg/kg
Sewage treatment plant		35.6 mg/L
Soil		90.3 µg/kg

propan-2-ol;isopropyl alcohol;isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release (freshwater)		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Predators		160 mg/kg

Sewage treatment plant		2.251 g/L
Soil		28 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

<i>General recommendations:</i>	Smoking, drinking and consumption of food is not allowed in the work area.
<i>Exposure scenarios:</i>	There are no exposure scenarios implemented for this product.
<i>Exposure limits:</i>	Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.
<i>Appropriate technical measures:</i>	<p>The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.</p> <p>Ensure that eyewash stations and safety showers are located within easy reach.</p> <p>Apply standard precautions during use of the product. Avoid inhalation of vapours.</p>
<i>Hygiene measures:</i>	Take off contaminated clothing and wash it before reuse.
<i>Measures to avoid environmental exposure:</i>	Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally: Use only UKCA marked protective equipment.

Respiratory Equipment:

Type	Class	Colour	Standards	
Respiratory protection is not				

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Type	Class	Colour	Standards	
needed in the event of adequate ventilation.				
A	Class 1 (low capacity)	Brown	EN14387	

Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	

▼ *Hand protection:*

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 480	EN374-2, EN16523-1, EN388	

Eye protection:

Type	Standards	
In the likelihood of direct or incidental exposure, use face protection.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	Transparent
<i>Odour / Odour threshold:</i>	Aromatic
▼ <i>pH:</i>	No data available.
▼ <i>Density (g/cm³):</i>	0.836
▼ <i>Kinematic viscosity:</i>	No data available.
<i>Particle characteristics:</i>	Does not apply to liquids.

Phase changes

▼ <i>Melting point/Freezing point (°C):</i>	No data available.
<i>Softening point/range (°C):</i>	Does not apply to liquids.
<i>Boiling point (°C):</i>	55-185
▼ <i>Vapour pressure:</i>	No data available.
▼ <i>Relative vapour density:</i>	No data available.
▼ <i>Decomposition temperature (°C):</i>	No data available.

Data on fire and explosion hazards

<i>Flash point (°C):</i>	-10
<i>Flammability (°C):</i>	200
▼ <i>Auto-ignition temperature (°C):</i>	No data available.
<i>Lower and upper explosion limit (% v/v):</i>	1 - 36.5

Solubility

▼ <i>Solubility in water:</i>	No data available.
-------------------------------	--------------------

▼ *n*-octanol/water No data available.

coefficient (LogKow):

▼ *Solubility in fat (g/L):* No data available.

9.2. Other information

▼ *VOC (g/L):* 836

Other physical and No data available.
chemical parameters:

▼ *Oxidizing properties:* No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

▼ STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

▼ STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

▼ Symptoms related to the physical, chemical and toxicological characteristics

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the

breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

11.2. Information on other hazards

▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3.

SECTION 12: ECOLOGICAL INFORMATION

12.1. ▼ Toxicity

Harmful to aquatic life with long lasting effects.

12.2. ▼ Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. ▼ Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. ▼ Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

▼ EWC code: 07 01 04* Other organic solvents, washing liquids and mother liquors

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/A DN/RI D	UN1263	PAINT RELATED MATERIAL	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1263	PAINT RELATED MATERIAL	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1263	PAINT RELATED MATERIAL	Transport hazard class: 3 Label: 3 Classification code: F1 	II	No	See below for additional information.

* Packing group

** Environmental hazards

▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<i>Restrictions for application:</i>	People under the age of 18 shall not be exposed to this product. Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.
<i>Demands for specific education:</i>	No specific requirements.
<i>SEVESO - Categories / dangerous substances:</i>	P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes
<i>▼ Regulation on drug precursors:</i>	acetone;propan-2-one;propanone is included (Category 3) butanone;ethyl methyl ketone is included (Category 3)

▼ <i>Regulation on explosives precursors:</i>	acetone;propan-2-one;propanone (Annex II)
▼ <i>REACH, Annex XVII:</i>	<p>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane is subject to UK-REACH restrictions (entry 40).</p> <p>reaction mass of ethylbenzene and xylene is subject to UK-REACH restrictions (entry 40).</p> <p>acetone;propan-2-one;propanone is subject to UK-REACH restrictions (entry 40).</p> <p>n-butyl acetate is subject to UK-REACH restrictions (entry 40).</p> <p>Hydrocarbons, C9, aromatics is subject to UK-REACH restrictions (entry 40).</p> <p>2-methoxy-1-methylethyl acetate is subject to UK-REACH restrictions (entry 40).</p> <p>propan-2-ol;isopropyl alcohol;isopropanol is subject to UK-REACH restrictions (entry 40).</p> <p>1-methoxy-2-propanol;monopropylene glycol methyl ether is subject to UK-REACH restrictions (entry 40).</p> <p>butanone;ethyl methyl ketone is subject to UK-REACH restrictions (entry 40).</p> <p>2-methylpropan-1-ol;iso-butanol is subject to UK-REACH restrictions (entry 40).</p> <p>ethyl acetate is subject to UK-REACH restrictions (entry 40).</p>
▼ <i>Labelling of contents according to Detergents Regulation (EC) No 648/2004:</i>	<p>≥15% - <30%</p> <ul style="list-style-type: none"> · Aliphatic hydrocarbons · Aromatic hydrocarbons
<i>Additional information:</i>	<p>Tactile warning.</p> <p>If this product is sold in retail, it must be delivered with child-resistant fastening.</p>
▼ <i>Sources:</i>	The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.
Regulation (EC) No 648/2004 on detergents as retained and amended in UK law.
Control of Major Accident Hazards (COMAH) Regulations 2015.
2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
The Controlled Drugs (Drug Precursors) Regulations 2008.
Council Regulation (EC) No 2019/1148 on explosives precursors as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

▼ Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H312, Harmful in contact with skin.

H315, Causes skin irritation.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H336, May cause drowsiness or dizziness.

H373, May cause damage to organs through prolonged or repeated exposure.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

PC 0 = Other products

▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EC = Effective concentration

ED = Effective dose

EINECS = European Inventory of Existing Commercial chemical Substances

EL = Effective Loading

ErC = Concentration associated with x% growth rate response

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

HP = Hazardous Property code

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IC = X maximum inhibitory concentration

IMDG = International Maritime Dangerous Goods

LC = Lethal concentration

LCLo = Value is the lowest concentration of a material in air reported to have caused the death of animals or humans

LD = Lethal dose

LOAEC = Lowest Observed Adverse Effect Concentration

LOAEL = Lowest Observed Adverse Effect Level

LOEC = Lowest Observed Effect Concentration

LogKow = logarithm of the n-octanol/water coefficient

LL = Lethal Loading

M = For multiplication factor

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NOAEC = No Observed Adverse Effect Concentration

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOELR = No Observable Effect Loading Rate

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

MSDS

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en