Product Information

EUROLUB
Efficiency in Fluids

EUROLUB
ECO STL 0W-30

Description

Car engine oil with significant fuel-saving potential. Ideally suited for vehicles with automatic start-stop systems.

Can be used with

Stellantis FPW9.55535-DH-1

Delivery

Art.-No. 390001	12 x 1 Liter	bottle
Art.-No. 390005	4 x 5 Liter	can
Art.-No. 390020	20 Liter	can
Art.-No. 390060	60 Liter	drum
Art.-No. 390208	208 Liter	drum
Art.-No. 390100	Container	800 – 3.000 litre
Art.-No. 390000	Bulk	from 3.001 litre

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.845
Viscosity at 40°C	mm²/s	DIN 51 562	53.4
Viscosity at 100°C	mm²/s	DIN 51 562	9.6
Viscosityindex (VI)	-	DIN ISO 2909	167
Flash point (COC)	°C	DIN ISO 2592	220
Pourpoint	°C	DIN ISO 3016	-51

Die angegebenen Daten können Änderungen unterliegen. Betriebsvorschriften des Herstellers beachten. Durch Weiterentwicklung von Produkt und Produktion bedingte Datenänderungen bleiben vorbehalten. Diese Angaben sollen das Produkt beschreiben und haben somit nicht die Bedeutung, bestimmte Eigenschaften zuzusichern. Eine Verbindlichkeit kann hieraus nicht abgeleitet werden.

KLIMANEUTRALES UNTERNEHMEN
certified by Fokus Zukunft